SCHEDA TECNICA SPC ORIGINAL

EP life®

ORIGINALS
COLLECTIONS

PRODUCT SPECIFICATION

DECOR	DIMENSIONS	EDGE	SURFACE	CLICK
	228 X 1220	MICRO BEVEL	EIR	UNICLIC PATENTED TECHNOLOGY
	Package(m^2)	Palette (m^2)	Container(20')	Warranty(Year)
PLANK	9 x ▬ = 2.503 m^2 = 20.20 kg	64 x ▤ = 160.220 m^2 = 1.292.80 kg	20 x ▤ ▤ = 3.204.40 m^2 = 25.856.00 kg	20

TECNICAL SPECIFICATION

	ICON	STANDARTS	SPECIFICATIONS
Surface treatment (UV)			Yes
Underlay		IXPE	1 mm
Total thickness		ISO24337	5 mm
Wear layer thickness		EN429	0.5 mm
Total weight		EN ISO 23997	8.00- kgs/sqm
Dimensional stability		TS EN ISO 23999	Class 34
Performance classification		23.34.43	
Residual indentation after static load		TS EN ISO 24343-1:2007	0.01 mm
Anti-slip resistance		EN 13893	DS
Electrostatic behavior		1815:2016	Anti static floor covering
Floor heating system		Suitable	Max.27^0
Antibacterial		ISO 22196	Antibacterial
Pet-friendly			Pass
Phthalate analysis		Inhouse Methot	Phatalete free
Formaldehyde emissions		EN 717-1:2004	E1
Fire behavior		EN13501-1 | EN 9239-1:2010	BFL-S1
Reaction to fire		EN 11925-2:2020	Bs-d0
Thermal resistance		EN 12667	0.296 W(m.K)
Matte Degree			2-4^0
VOC emissions		FloorScore CE	Certified
Impact Sound Transmission		ASTM E492-09:2016 - ASTM E989-18	IIC=75dB
Airborne sound transmission loss		ASTM E413-16	R_w+C=75dB - STC = 73dB